

NAUTILUS FLOATS

FOR PIPE, HOSE OR CABLE

With GripTite™ Technology

www.nautilusfloats.com



Patent Pending



Kevin, Project Manager - Callan Marine reports:
“Dredge Captains love them - they do not move at all on the pipe, or rotate. Hydrodynamically, the floats are fantastic. When the dredge moves from place to place in the course of it’s work, the floats stay in position.”



NAUTILUS™ FLOATS

Nautilus Floats, LLC

Phone +1 325-646-1566

Fax: +1 325-643-4644

sales@nautilusfloats.com

nautilusfloats.com

Features

Tongue and groove profile locks assembly together.



Tapered nose design reduces drag on float.


Corner bolt pattern secures floats tightly to the pipe.



Top ribs allow floats to be stacked for storage or shipment.

Patent Pending

Configuration of the inner core is a multi-faceted gripping surface that channels fluids between the pipe and float providing more contact area to a pipe than standard designs. No rubber inserts or gaskets necessary.



The Nautilus family of floats can be used foam filled or unfoamed for specific applications.

Part No.	Pipe Size inches (mm)	Overall Dia. inches (mm)	Overall Length inches (mm)	Bolts/Set	Weight lbs.(kg)	Flotation Capacity @50% submersion
4440600F92602	6" (152)	24 (610)	42 (1066)	6	65 (29.5)	215 (97)
4440800F92602	8" (203)	24 (610)	42 (1066)	6	65 (29.5)	204 (92)
4441000F92602	10" (254)	32 (812)	36 (914)	6	81 (36.8)	315 (143)
4441200F92602	12" (305)	32 (812)	40 (1016)	8	88 (40)	330 (150)
4441400F92602	14" (356)	32 (812)	45 (1143)	8	99 (45)	355 (161)
4441600F92602	16" (406)	45 (1143)	45 (1143)	8	160 (72.5)	745 (338)
4441800F92602	18" (457)	45 (1143)	45 (1143)	8	165 (75)	765 (347)
4442000F92602	20" (508)	46.5 (1181)	45 (1143)	8	187 (85)	820 (372)
4442200F92602	22" (559)	46.5 (1181)	45 (1143)	8	187 (85)	804 (365)
4442400F92602	24" (610)	48 (1219)	45 (1143)	8	193 (87.7)	825 (375)

All dimensions and weights are approximate.



Nautilus Floats, LLC

Phone: +1 325-646-1566

Fax: +1 325-643-4644

sales@nautilusfloats.com

nautilusfloats.com